

Datasheet

Type: OS0062 T8 LED TUBE
Itemnr.: 9909040830003



Size	A	B	C
600	604	588.5±1	533.5
900	908.8	893.5±1	838
1200	1213.6	1198±1	1143.16
1500	1514.2	1499±1	1443.5

Technical Data

Lumen	1710m, 2250lm or 3240m
Beam Angle	105 (Typical UGR 16-20)
Colors Available	Warm white or Neutral white
Color Temperature	3000K, 4000K or 5000K
Color Rendering	CRI80+
MacAdam	Step 4 (option Step 3)
Color Bin	V6
Consumption	9.5W, 12.5W or 18W
Voltage Range	220 ~ 240VAC 50/60Hz
10A Fuse Type C	Max. 44 luminaires (Start Current limit)
16A Fuse Type C	Max. 62 luminaires (Start Current limit)
Efficiency	180 LPW
Equal To	OS0062 12W = Fluorescent tube T8 36W
Lifetime	50K hours at Ta = 25°C (L70) B10
IP Code	IP20
Class	2, Double Insulated
Size	Ø28 x L600, 900, 1200 or 1500 mm
Installation	Exciting fluorescent tube luminaires
Material used	PC, Steel
Weight	0,125 Kg, 0,235 Kg or 0,310 Kg
Shipping	Package of 30 pcs
IES File	Yes
Warranty	5 years*
Housing	White
Included	LED Tube, LED starter

Lumega Europe ApS
Phone +4571995825
info@lumega.eu
www.lumega.eu