

Datasheet

Type: OS0073 LED Retrofit
Itemnr.: 9909031830003



Technical Data

Lumen	4500lm or 6300lm
Beam Angle	280 / 340 dg
Colors Available	Warm white, Neutral white, Cold white
Color Temperature	3000K, 4000K, 5000K
Color Rendering	CRI75
MacAdam	Step 5
Consumption	30W or 40W
Voltage mains	100 ~ 240VAC 50/60Hz
Current LEDs	300mA - 700mA
Power factor	>90
10A Fuse Type C	Max. 22 luminaires (Start Current limit)
16A Fuse Type C	Max. 44 luminaires (Start Current limit)
Leakage current	< 0,5mA @ 240V AC
Efficiency	150 LPW (LEDs 172 LPW)
Equal To	LED 40W = Metal halide 70W HIT
Lifetime	50K hours at Ta = 25°C (L70) B10
Dimmable	No
IP Code	IP65 (except base)
IK Class	IK00
Class	2, Double Insulated
Working temp	-30 to 50 degree Celsius
Size	See sketches on the left
Base	E27
Installation	Installed in exciting park og street luminaire
Linkable cables	N/A
Material used	Aluminum, PMMA for frontglass
Weight	0,3 Kg
Shipping	Package of 25 pcs
IES File	Yes
Certificates	CE, ROHS, LM80, LM79, IES
Warranty	3 years*
Housing	Aluminum color

Lumega Europe ApS
Phone +4571995825
info@lumega.eu
www.lumega.eu